

## KEY FEATURES

- Intel® Celeron® M 1.86GHz, 1MB L2 Cache
- Die-Cast Aluminum Alloy Housing for maximum heat diffusion
- Operates in a wide range of environments and temperatures. 14° F ~ 122° F (-10° C ~ 50° C)
  - -10° C ~ 45° C with Hard Drive Disk
  - -10° C ~ 50° C with Solid State Drive
- 2GB of DDR2 Memory
- Precisely designed, with strict revision control to maximize the system's lifecycle
- Stringent third party tested for superior vibration resistance
- Liquid/Splash Resistant



## KS7300 Series

### About Posiflex

Designer and manufacturer of Point-of-Service and industrial touch terminals

Revolutionary technology, reliable quality, reasonable pricing and recognized service

Delivers reliable terminals for maximum uptime and lower total cost of ownership

Comprehensive suite of peripherals and services

Over 25 years of excellence

Global presence

Over 30 patents for innovation

Two ISO 9001/9002/14001 Certified Facilities

### Power-Performer

One of the latest additions to the popular fan-free KS Series combines optimal performance, low power consumption and heat output with ease of maintenance.

The “green” footprint allows companies or divisions to meet corporate mandates related to the development of energy saving systems and devices.

The KS7300 is available in 15” and 17” Infrared or Resistive touch options. Both models are configurable to wall mount solutions and are optimized for retail, quick service, full service hospitality, grocery and specialized markets.

**For more information call 888.968.1668 today!**

# Specifications

SPECIFICATIONS		KS7315	KS7317	AVAILABLE SERVICES
Processor	Intel® Celeron® M 1.86GHz, 1MB L2 Cache			<ul style="list-style-type: none"> <li><b>Standard and Extended Warranty</b> Extend your depot warranty up to 5 years.</li> <li><b>Advance Exchange</b> We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.</li> <li><b>OnSite Service</b> Expert technicians will efficiently handle the complete equipment swap and return process.</li> <li><b>Regional Repair Depots</b> Three regional depots assure fast turn-around time on repairs.</li> <li><b>Post Warranty Support</b> Spare parts, in addition to a flat rate repair program, for post warranty needs.</li> <li><b>Installation Services</b> Let our nationwide network of experts stage and install your equipment.</li> <li><b>OEM Design and Integration</b> Our Product Development Team helps design equipment, for custom hardware applications.</li> </ul>
System Memory	DDR2 667 MHz, SO-DIMM socket x 1 (2GB Default)			
Maximum Memory	2GB			
Power Supply	12V DC Power adaptor, 80W			
Storage Device	2.5" SATA 160GB HDD or SSD Kit (optional)			
Supported OS	POSReady / WinXP Pro / Win7 Pro (32) / Linux			
<b>DISPLAY</b>				
LCD	15" TFT LCD, 1024x768   17" TFT LCD, 1280x1024			
Touch Function	5-Wire Resistive or Infrared, USB Interface			
Brightness Control	Digital Push Button			
Tilt Adjustment	15° to 70°			
<b>PHYSICAL DIMENSIONS</b>				
Dimensions (WxDxH)	14.76" x 15.20" x 15.55"			
Weight (Pounds)	20 lbs			
<b>CONNECTIVITY</b>				
LAN Port	10/100/1000 Base-T Ethernet			
Serial Port	DB9 x 4 (5V/12V support on COM1/COM2/COM3/COM4)			
Backup Battery Port	1 Port (Battery Optional)			
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD Monitor			
CR Port	CR x 1 (Controls 2 drawers)			
Standard USB Port(s)	6			
Parallel Port	Yes			
<b>PERIPHERALS</b>				
Magnetic Stripe Reader - SD404 Biometric or Encrypted options 	Rear Mount Display - PD310 2 x 20 Character VFD* 	Thermal Printer - PP8000 80mm Wide, Printing Speed: 220mm/second 	Cash Drawer - CR6300 Printer Driven and USB options available 	

\*Vacuum Fluorescent Display

See [www.PosiflexUSA.com](http://www.PosiflexUSA.com) for a complete line of peripherals

**POSIFLEX™**  
 Be the Pioneer, Be the Leader  
 30689 Huntwood Avenue  
 Hayward, CA 94544  
 Toll-free: 888.968.1668  
 Phone: 510.429.7097  
 Fax: 510.475.0982  
 E-mail: [sales@posiflexusa.com](mailto:sales@posiflexusa.com)  
[www.posiflexusa.com](http://www.posiflexusa.com)

