



# The new RP 3200 STAR. The retail printer that rules its category.



**Print speed of  
200 mm/sec in both  
text and graphic mode -  
Prints up to 60 bills/minute**



**Auto-cutter - 1.5 Million  
cuts; tear your bills neatly**



**Supports Windows 8**



**Energy star qualified  
for power efficiency**



**Print head life of  
160 km**



**4 in 1 connectivity - Interface  
options : USB Standard  
(Optional : Parallel, Serial,  
Ethernet & Wi Fi)**

## The RP 3200 STAR Advantage

Today, the retail sector is changing rapidly – in both technology and service. Efficiency and speed are the keys to satisfying and retaining customers. That's why the new RP 3200 Star, with a print speed of 200 mm/sec, is one of the fastest in its category. It is Energy Star Level 5 qualified, decreases power consumption by 29 % and supports Windows 8 along with existing platforms. The RP 3200 Star not only comes with a built-in auto-cutter (with an improved life of 2 million cuts) but also USB connectivity and one other optional card (serial, parallel, WIFI or Ethernet).

Upgrade your billing standards now with RP 3200 Star, the thermal bill printer.

## Specifications - RP 3200 STAR

Printing Method	: Direct thermal
Printing Speed	: 200 mm/sec
Dot Density	: 180 dpi
Dot Pitch	: 0.141mm
Character Per Line	: Font A-42 columns; Font B-56 columns
Character Set	: Alphanumeric characters 95, extended graphic 128 x 7 page (1 space page), international characters 32
Barcode Fonts	: UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), CODE 39, CODE 93, CODE 128, ITF, CODABAR, PDF 417, QR-CODE
Paper Width	: 50 mm - 82.5 mm
Paper Thickness	: 0.06 ~ 0.09 mm
Paper Roll Diameter	: Max. ~ 80.0 mm
Roll Core Inner Diameter	: 12.5 mm ±0.5 mm
Printing Width	: 72 mm, 512 dots/line
Interface	: USB + 1 selectable type ( Parallel, Serial, Ethernet, Wi Fi)
Flash Memory	: 4 MB (32 MB Optional)

Logo Printing	: 1.3 MB memory for logo storing
Emulation	: ESC / POS
Driver	: Windows Printer Driver (8,7,XP,2000,2003,VISTA),WEPOS, Linux, OPOS, Java POS
Cash Drawer	: 1 Port
Reliability (Print Head Life)	: 160 km
MCBF	: 60,000,000 Lines
Sensor	: Paper End, Paper Low, Cover Open
Physical Dimensions (W x D x H)	: 152 x 202 x 150.5 mm
Auto Cutter Type	: Guillotine
Life	: 1,500,000 cuts
Cutting Method	: Full / partial cut
Power Supply	
AC	: 100V - 240V, 50/60 Hz
DC	: 24 Vdc/ 1.75 A
Operating Temperature	: 0° ~ 40°C
Storage Temperature	: -20° ~ 60°C
Operating Humidity	: 35% ~ 80%
Storage Humidity	: 10% ~ 90%
Warranty	: 1 year
Weight	: 1.7 kg

## Best suited for printing

Bills | Receipts | Tickets / Gate Passes | Coupons / Tokens

## CUSTOMER SEGMENTS



Supermarkets



Grocery Shops



Restaurants & Bars



Fast Food Joints



Airport



Lottery



Ticketing



Toll Gates

## ORDERING INFORMATION

3006400002 RP 3200 STAR

## OPTIONAL ACCESSORIES

SERIAL CARD

PARALLEL CARD

ETHERNET CARD

WIFI CARD